

WALL MOUNT

WM103 Series

DECORATIVE WALL MOUNT
Indoor/Outdoor — FL, IND, LED, HID

SERIES

WM103 WM103 9.25" Deep Series

STYLE

- A Cage Free
- B Cage with Eyelid
- C Cage: 1 Vert/Hor Bar
- D Cage: 2 Vert/Hor Bar

LAMP TYPE

- DBX Double Biax Mini-Fluorescent
- TBX Triple Biax Mini-Fluorescent
- QL QL Induction
- MH Metal Halide
- LED Light Emitting Diode

VOLTAGE

- 120 120 Volts
- 277 277 Volts
- 347 347 Volts
- QV Quad Volt
- UNV 120~277 Universal Volt
Must Specify Voltage for EM option

BALLAST

- EBX Electronic Ballast
- 2EBX Two Electronic Ballasts
- EBMH Electronic Ballast for MH
- HPF High Power Factor for MH

OPTIONS

- CT3 ±3000K LED Color Temp
- CT4 ±4000K LED Color Temp
- CT5 ±5000K LED Color Temp
- DIM Dimming Ballast
**Refer to DIM Table for options*
- EM Integral Emergency Battery
*- Must Specify Voltage [120V or 277V];
Refer to EM Table for options]
- FG Frosted Glass Lens [req'd with LED]
- FUS Fuse and Fuseholder
- FUS2 Double Fusing
- GN Generator Transfer Device
- H/L Dual Circuit, High/Low LED Light Level
- LEC5* LED Emergency Circuit [1] Five Watt
- LEC10* LED Emergency Circuit [2] Five Watt
**Must Specify Voltage for incoming EM Circuit [by others]
A = 12VDC or B = 120VAC or C = 24VDC or D = 277VAC*
- MD Integral Motion Detector for LED
- MDX External Motion Detector for LED
Specify Finish: Bronze or White
- REM Remote Emergency Battery
*self-contained in CA
- Must Specify Voltage [120V or 277V];
Refer to EM Table for options]
- SRM Semi-Recessed [MH70W Max]
- TPD Tamperproof Screwdriver

FINISH

- BK Black
- BZ Bronze — Standard
- PA Painted Aluminum
- WHT White



WM103 LAMPING TABLE

DBX	TBX	MH	QL	LED
[2]26	[1-2]26 [1-2]32 [1-2]42 [1]57	[1]50 [1]70 [1]100	[1]55	15 30 40

SPECIFICATIONS

Superb combination of classic styling, spec-grade construction, and energy-efficient illumination. Luminaires provide smooth, wide spread accent and security lighting with superior weather & vandal-resistant design features.

- BALLAST — High Power Factor 120 or 277 Volt Electronic Ballast. Pulse Start MH.
- FINISH — Oven baked [BZ] bronze polyester powder finish
- GASKETING — High temperature black EPDM and neoprene rubber concealed in housing pocket & enclosed by cast in drip shield and rear wire entrance hole protects against dust, moisture and outside contamination.
- HOUSING — Heavy wall cast aluminum. Wire access on 4 sides and back through .5" conduit size threaded entrance holes.
- LAMP — [DBX] Double Biax, [TBX] Triple Biax; [MH] Metal Halide; [LED] Light Emitting Diode.
- LENS — Durable Molded Borosilicate Glass Lens.
- LENS FASTENERS — 4 Stainless steel tamperproof screws to secure lens in place.
- LABELS — **UL/ULC LISTED** Suitable For Wet Location.
- REFLECTOR — Textured .032 aluminum for high efficiency and reduction in arc tube voltage rise.



SUBMITTAL INFORMATION

Project: _____

Location: _____

Catalog No.: _____

Fixture Type: _____