

WALL MOUNT

WM104 Series

HIGH ABUSE WALL MOUNT LUMINAIRE
Indoor/Outdoor — FL, IND, LED, HID

SERIES	
WM104	WM104 Series
LAMP TYPE	
DBX	Double Biax Mini-Fluorescent
TBX	Triple Biax Mini-Fluorescent
MH	Pulse Start Metal Halide
MHC	CosmoPolis™ Metal Halide Ceramic by Philips
MHE	Elite™ Metal Halide Ceramic by Philips
QL	QL Induction
LED	Light Emitting Diode
VOLTAGE	
120	120 Volts
277	277 Volts [277V Stnd for MHC & MHE]
347	347 Volts (Consult Factory)
QV	Quad Volt [120/208/240/277]
UNV	120~277 Universal Volt <i>Must Specify Voltage for EM option</i>
BALLAST	
EBX	Electronic Ballast/Driver
EBMH	Electronic Ballast for MH
HPF	High Power Factor for MH
OPTIONS	
CT3	±3000K LED Color Temp
CT4	±4000K LED Color Temp
CT5	±5000K LED Color Temp
CPG	Clear Polycarbonate Guard
DIM	Dimming Ballast <i>*Refer to DIM Table</i>
DS	Dark Sky/Full Cut-Off - Down Light Only <i>[NOT Avail. for W2-14]</i>
EM	Integral Emergency Battery <i>- Must Specify Voltage [120V or 277V]; *Refer to EM Table for options]</i>
FUS	Fuse and Fuseholder
FUS2	Double Fusing
GN	Generator Transfer Device
H/L	Dual Circuit, High/Low Light Level for LED
MDX	External Motion Detector <i>Specify Finish: Bronze or White</i>
PHT1	Integral Photocell 120V
PHT7	Integral Photocell 277V
REM	Remote Emergency Battery <i>self-contained in CA - Must Specify Voltage [120V or 277V]; *Refer to EM Table for options]</i>
TPD	Tamperproof Screwdriver
SCO	Side Cut-Off
SU	Surge Protection for LED fixtures
WG	Stainless Steel Wire Guard
FINISH	
BK	Black
BZ	Bronze - Standard
CC	Custom Color
SV	Silvadillo Gray
WHT	White


WM104 LAMPING TABLE

DBX	TBX	MH	MHC	MHE	QL	LED
(2)26	(2)32	[1]150	[1]60	[1]210	[1]55	60
	(2)42	[1]175	[1]90	[1]315	[1]85	80
	(1)57	[1]250	[1]140		[1]165	
	(1)70	[1]400				

SPECIFICATIONS

Superb combination of classic styling, spec-grade construction and energy efficient illumination. High Abuse Series luminaires provide smooth, wide spread accent and security lighting with superior weather and vandal-resistant design features.

- **BALLAST** — 120 or 277 Volt, extreme temp range -30°C to 90°C, HPF electronic ballast [EBX].
- **DIFFUSER** —
- **FINISH** — Textured Bronze oven baked polyester powder coat.
- **GASKETING** — High temp anti-age black EPDM and/or neoprene rubber around lens perimeter & rear wire entrance hole, protects from dust, moisture and outside contamination.
- **HOUSING** — Heavy wall cast aluminum with wire access on 2 sides, top and back through .5" conduit size entrance holes.
- **HOUSING OPTIONS** — Available as Down Light Only [DS] to preserve true Dark Sky; Vandal Resistant features enhanced with Wire Guard [WG] or Clear Polycarbonate Guard [CPG].
- **LENS** — Borosilicate molded glass.
- **LABELS** — **UL/ULC LISTED** Suitable For Wet Location.
- **REFLECTOR** — .032 aluminum for high efficiency and reduction in arc tube voltage rise.



SUBMITTAL INFORMATION

Project: _____

Location: _____

Catalog No.: _____

Fixture Type: _____